

## LSZH copper wire braided screen flexible control cable, 300/500V CU/LSZH/CWB/LSZH

No. of cores	Nominal area	Insulation thickness	Outer sheath thickness	Approx. overall diameter	Approx. weight
No.	mm <sup>2</sup>	mm	mm	mm	(kg/km)
2	0.5	0.4	0.6	7.3	80.1
2	0.75	0.4	0.6	7.7	90.6
2	1	0.4	0.7	8.1	102.4
2	1.5	0.4	0.7	8.7	121.2
3	0.5	0.4	0.6	7.5	88.6
3	0.75	0.4	0.7	8.2	106.5
3	1	0.4	0.7	8.4	117.4
3	1.5	0.4	0.7	9	140.3
3	2.5	0.5	0.8	10.5	195.3
4	0.5	0.4	0.7	8.2	105.7
4	0.75	0.4	0.7	8.7	122.6
4	1	0.4	0.7	8.9	135.9
4	1.5	0.4	0.7	9.6	165.4
4	2.5	0.5	0.8	11.3	234.3
4	4	0.6	1	13.1	328.7
4	6	0.65	1.1	15	456.6
4	10	0.75	1.3	18.5	715.9
4	16	0.75	1.5	21.3	1014.5
4	25	0.9	1.6	25.7	1490.5
4	35	0.95	1.7	29.1	2009.1
5	0.5	0.4	0.7	8.6	117.8
5	0.75	0.4	0.7	9.2	138.6
5	1	0.4	0.7	9.4	154.7
5	1.5	0.4	0.8	10.4	195.4
5	2.5	0.5	0.9	12.3	279.5
5	4	0.6	1.1	14.5	411.9
5	6	0.65	1.2	16.3	546.7
5	10	0.75	1.4	20.2	864.6
5	16	0.75	1.5	23.1	1221.1
5	25	0.9	1.7	28.7	1874.8

\*The information in this datasheet is for reference only and is subject to change without notice or liability.